

Pipe, Tube and Hose Cleaning System



Characteristics

Simple and low cost solution for the removal of unwanted contaminant from the inside surfaces of pipes, tubes and hoses

The STAUFF Clean system comprises of a pneumatic launcher and a range of specially designed nozzles. The launcher uses standard industrial compressed air in pressure between 6 and 8 bar / 87 and 116 PSI to propel a foam projectile through the nozzle and into the hose, tube or pipe to be cleaned. This provides a safe and environmentally friendly tool that requires little formal expertise to operate and apply.

The launcher is the part of the system that controls the air supply to propel the projectile from start to finish of the cleaning job.

The nozzles are specially designed to affect an airtight seal on any pipe, tube or hose with or without end fittings. Its main purpose is to compress the foam projectile allowing it to enter the internal diameter of the pipe, tube or hose to be cleaned.

The projectile is the part of the system that does the cleaning: The foam projectile is sized to be approximately 15 % larger than the internal diameter of the pipe, tube or hose to be cleaned. The compression of the projectile against the internal wall cleans the internal surface and expels any loose contaminants from the end of the pipe, tube or hose.

The STAUFF Clean System is available as separate components or in a variety of kit forms comprising various nozzle types, adaptor and launcher, all contained in a heavy duty carrying case.

Launchers / Launcher Kits



Characteristics

Features

- Pneumatic pistol-grip launcher
- Light-weight and ergonomic design
- Easy to operate and apply
- Connection to air supply with quick release coupling
- Suitable for any type of nozzle
- Delivered separately or in a variety of kit forms including carrying case, adaptor ring and nozzles (if required)

Technical Data

- Air compressor requirement: 6 ... 8 bar / 87 ... 116 PSI
- Effective air volume: 250 ... 400 l/min / 66 ... 106 US GPM

Order Codes

▪ Launcher only	SC-LG-1
▪ Launcher kit without nozzles	SC-LK-1
▪ Launcher kit with set of 10 Universal nozzles	SC-10UV-K
▪ Launcher kit with set of 18 Metric Tube nozzles	SC-18MT-K
▪ Launcher kit with set of 10 JIC nozzles	SC-10J-K
▪ Launcher kit with set of 7 BSP nozzles	SC-7B-K
▪ Launcher kit with set of 7 NPT nozzles	SC-7N-K
▪ Adaptor ring	SC-UV-AR

Consult STAUFF for special connection adaptors and couplings.

Nozzles / Nozzle Sets



If required, nozzles can also be supplied separately. Consult STAUFF for availability and order codes.

Universal Nozzle Set (Order Code: SC-10UV-S)

The Universal Nozzle is designed with a tapered seat that will allow it to suit for 90% of applications, including Hose, Tube and Pipe, with or without fittings, in hydraulic and pneumatic pipe systems, condenser tubes, boiler tubes and food lines.

The Universal Nozzle kit fits all and will accommodate applications with JIC, SAE and BSP end fittings.

The set of 10 nozzles consists of the following sizes: 6 mm, 8 mm, 10 mm, 13 mm, 16 mm, 19 mm, 25 mm, 32 mm, 38 mm and 50 mm.

Metric Tube Nozzle Set (Order Code: SC-18MT-S)

The Metric Tube Nozzle is intended for use specifically with Metric sized tube and is designed to fit over the outside of the tube or pipe being cleaned.

The inside diameter of the nozzle is reduced to match the inside diameter of the tube. The nozzles are machined from solid bar stock and designed for superior strength.

The set of 18 nozzles consist of the following Metric OD sizes: 6 mm, 8 mm, 10 mm, 12 mm, 14 mm, 15 mm, 16 mm, 18 mm, 20 mm, 22 mm, 25 mm, 28 mm, 30 mm, 35 mm, 38 mm, 42 mm, 50 mm and 60 mm.

JIC Nozzle Set (Order Code: SC-10J-S)

The JIC Nozzle is designed specifically for use with JIC and SAE type fittings. The nozzles are machined to accommodate both male and female configuration, ensuring a perfect airtight seal every time.

The set of 10 nozzles consist of the following sizes: 6 mm, 8 mm, 10 mm, 13 mm, 16 mm, 19 mm, 25 mm, 32 mm, 38 mm and 50 mm.

BSP Nozzle Set (Order Code: SC-7B-S)

The BSP Nozzle is designed specifically for BSP configuration fittings. The nozzles are machined to accommodate both male and female configurations, ensuring a perfect airtight seal every time.

The set of 7 nozzles consist of the following sizes: 6 mm, 10 mm, 13 mm, 16 mm, 19 mm, 25 mm and 32 mm.

NPT Nozzle Set (Order Code: SC-7N-S)

The NPT Nozzle is designed specifically for NPT configuration fittings. The nozzles are machined to accommodate both male and female configurations, ensuring a perfect airtight seal every time.

The set of 7 nozzles consist of the following sizes: 1/4 in, 3/8 in, 1/2 in, 5/8 in, 3/4 in, 1 in and 1-1/4 in.

Projectiles


Standard Series (S)

Standard Series Projectiles are intended for the cleaning of hose, tube or pipe without end fittings or restrictions.


Coupling Series (C)

Coupling Series Projectiles are intended for the cleaning of hose assemblies (hose with end fittings, adjustments, etc.) or the removal of loose particles from pipe or tube.


Abrasive Series (A)

Abrasive Series Projectiles are intended for the cleaning of metal pipe and tube to remove light rust and scale. They are recognised by the abrasive pad fixed to one end of the projectile.


Grinding Series (G)

Grinding Series Projectiles are intended for the cleaning of metal pipe and tube to remove medium and heavy rust and build up from the internal surface. They are coated in Silicon Carbide.

Pipe O.D. (mm)	Pipe/Hose I.D. (mm/in)	Order Codes Standard Series (S)	Order Codes Coupling Series (C)	Order Codes Abrasive Series (A)	Order Codes Grinding Series (G)	Packaging Units (Projectiles / Order Unit)
07	4,8 3/16	SC-S-07	SC-C-07	SC-A-07	SC-G-07	100
09	6,35 1/4	SC-S-09	SC-C-09	SC-A-09	SC-G-09	100
10	6,35 1/4	SC-S-10	SC-C-10	SC-A-10	SC-G-10	100
12	7,9 5/16	SC-S-12	SC-C-12	SC-A-12	SC-G-12	100
14	9,5 3/8	SC-S-14	SC-C-14	SC-A-14	SC-G-14	100
16	11,1 7/16	SC-S-16	SC-C-16	SC-A-16	SC-G-16	100
18	12,7 1/2	SC-S-18	SC-C-18	SC-A-18	SC-G-18	100
20	14,28 9/16	SC-S-20	SC-C-20	SC-A-20	SC-G-20	100
22	15,88 5/8	SC-S-22	SC-C-22	SC-A-22	SC-G-22	100
26	19,05 3/4	SC-S-26	SC-C-26	SC-A-26	SC-G-26	50
28	20,64 13/16	SC-S-28	SC-C-28	SC-A-28	SC-G-28	50
30	22,23 7/8	SC-S-30	SC-C-30	SC-A-30	SC-G-30	40
33	25,4 1	SC-S-33	SC-C-33	SC-A-33	SC-G-33	40
36	26 / 27 1-1/16	SC-S-36	SC-C-36	SC-A-36	SC-G-36	30
38	28,58 1-1/8	SC-S-38	SC-C-38	SC-A-38	SC-G-38	30
40	31,75 1-1/4	SC-S-40	SC-C-40	SC-A-40	SC-G-40	30
45	34,93 1-3/8	SC-S-45	SC-C-45	SC-A-45	SC-G-45	20
50	38,1 1-1/2	SC-S-50	SC-C-50	SC-A-50	SC-G-50	20
55	44,45 1-3/4	SC-S-55	SC-C-55	SC-A-55	SC-G-55	15
60	50,8 2	SC-S-60	SC-C-60	SC-A-60	SC-G-60	10

Please note: For optimum cleaning, it is recommended that projectiles are used once and then discarded.

Safety note: A mesh collection bag should be secured to the pipe, tube or hose exit to avoid possible injury to personnel by the projectile exiting at high velocity.

Always wear protective safety glasses, ear protection and a dust mask when operating this device.